

# Thermion® Thermal Spray Wires



## Hard Surface Wear Resistant

Material Composition	Part #	Diameter	Packaged	Weight
<b>Nickel</b>				
<b>A1800</b>	TH208	1/16" (1.6mm)	Spool	25# (11.34kgs)
<b>Tungsten Carbides and Borides</b>	TH250	1/16" (1.6mm)	Spool	25# (11.34kgs)

Material Composition	Part #	Diameter	Packaged	Weight
<b>Stainless</b>				
<b>Stainless Steel 309</b>	TH309	1/8" (3.2mm)	Spool	25# (11.34kgs)
<b>Stainless Hard Facing</b>	TH351	1/16" (1.6mm) 3/32" (2.3mm)	Spool	25# (11.34kgs)
<b>Stainless Chrome Carbide</b>	TH353	1/16" (1.6mm)	Spool	25# (11.34kgs)
<b>Stainless HF Amorphous</b>	TH451	1/16" (1.6mm) 1/8" (3.2mm)	Spool	25# (11.34kgs)

For more information, please contact us at +66 (0)81-912-3299 or +66 (0)89-132-2132  
E-mail : [info@hmbcorp.com](mailto:info@hmbcorp.com) or [luksanac@hmbcorp.com](mailto:luksanac@hmbcorp.com)